

# Export Paint

## Bulk Blended Latex Paint Specifications

**Product Description:** All Acrylatex paints are made from name brand American latex/acrylic paint, over runs and mistints. We bulk blend and sort by color with extensive quality control and packaged in 275 gallon totes (1040L) for export. May be used on wood, stucco, masonry and drywall.

**Quality Control:** Our paints are rigorously tested for viscosity, adhesion, coverage, hide and pH. Before packaging we add preservatives and filter for a consistent high quality, smooth and clean product.

**Drying Time:** To touch 30 - 60 minutes depending on temperature and humidity. Good ventilation will decrease drying time.

**Thinning:** Use at supplied consistency. If thinning is required use water not to exceed a half pint per gallon.

**Clean up:** Use warm soapy water for hands and tools.

**Coverage:** 300 to 350 sq. Ft./gal. on smooth surfaces.

**Surface Preparation:** All surfaces must be free of dirt, oil, soot, loose and peeling paint. Remove all wallpaper and all glue before painting. Patched holes should be sanded smooth and primed first.

**Application:** Apply at temperatures above 50 degrees F. but not in extreme heat. Stir thoroughly before use. May be brushed, rolled or sprayed. Do not apply when rain, mist or fog may damage fresh paint film. For interior or exterior use.



### Composition/Properties:

Titanium Dioxide: 10-15%	Resin: 20-40%
Fillers/Extenders: 40-45%	Additives: 5-10%
VOC < 250 g/L	Viscosity: 92 - 95 KU
Gloss: 1 - 10%	Density: 1.2 - 1.4

Non Hazardous, water based paint.

**Safety Precautions:** Avoid breathing both vapors and mist during the application process. Avoid contact with eyes and skin. Wash thoroughly after handling this product. Refer to Material Safety Data Sheet for more detailed health and safety tips and recommended storage, transportation and disposal guidelines. In case of spill or uncontrolled release, absorb with inert material and dispose of according to local, state and federal codes.

Manufactured by:



### Typical Truckload/Container Configuration:

14 - 275 gallon totes (3,850 gal. - 14,550 L)  
with 2 green, 2 blue, 2 red, 4 tan, 2 off white, 1 yellow,  
2 gray and 1 brown totes.

U.S. funds, wire transfer only.